

# HERITAGE CARPETS

# TIFFANY TIFFANY //



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

MANUFACTURED IN CHINA //

## TECHNICAL SPECIFICATIONS //

FIBRE	100% Solution Dyed Nylon Made in Italy by Aquafil® SpA
CONSTRUCTION	1/10" Inch Loop Pile
PILE HEIGHT	ca. 3.0mm (+/-0.1mm)
STITCH RATE	43 per 10cm
PILE WEIGHT	ca. 750g/m2 (22 oz/y2)
TOTAL WEIGHT	ca. 4070g/m2 (120 oz/y2)
BACKING	ECO Cushion Backing (PVC-Free)
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	20 pc (5 m2)
INSTALLATION	Surface Tackifier
WEAR WARRANTY	10 Year Limited Wear Warranty

## PERFORMANCE SPECIFICATIONS //

As tested & certified by I.T.T.S. Inc., U.S.A.

FLAMMABILITY: Radiant Panel ASTM-E-648	Class 1 (ASTM-E-648)
FLAMMABILITY: Methanamine Pill ASTM-D-2859	Self-Extinguishing
FLAMMABILITY: Smoke Density ASTM-E-662	<= 450
TUFT BIND (ASTM-D-1335)	10.3 lbs
STAIN RESISTANCE	10 No residual stain (AATCC-175-1993)
LIGHTFASTNESS (AATCC 16E)	5 (Negligible or no change)
COLORFASTNESS TO OZONE (AATCC-165)	5 (Negligible or no change)
DIMENSIONAL STABILITY (AACHEN TEST)	<= 2.4%
RECOMMENDED USAGE	Medium Commercial Use
RECOMMENDED INSTALLATION METHOD	Ashlar, Brick and Quarter Turn

## INSTALLATION GUIDELINES //

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load bearing. The manufacturer recommends that the carpet tiles be installed in a "checker board" pattern, that is, every 2nd carpet tile should be turned 90° to the tile laid prior to it. If uni-effect is desired, the tiles should be installed with the arrows in the same direction. However, the seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles.

## ENVIRONMENT//

The design and production of Tiffany Tile conforms to the ISO 14001:2004 Environmental Management System and complies with environmental regulations. Tiffany Tile is an environmentally friendly "green" carpet.