

# HERITAGE CARPETS

## LINE-UP //



SUITABLE FOR MEDIUM CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

### TECHNICAL SPECIFICATIONS //

Construction	1/10" Looppile
Pile material	50% PA Solution Dyed - 50% PA Solution Dyed Space
Secondary backing	Back2Back: Modified bitumen enhanced with a thermoplastic elastomer, reinforced with a glass fibre fleece covered with 100% PES fleece. 10% recycled content included.
Total weight	Ca. 4.400 g/m <sup>2</sup>
Pile weight	Ca. 550 g/m <sup>2</sup>
Pile height	Ca. 2,5 mm
Pile above backing	Ca. 309 gr/m <sup>2</sup>
Total height	Ca. 5,7 mm
Tuft density	Ca. 168.000/m <sup>2</sup>
Thermal resistance	0,039 qm K/W
Impact noise rating	22 dB
Permanent antistatic	≤ 2 kV
Size	50cm x 50cm   60cm x 60cm (on request)
Packing	Box: 5 m <sup>2</sup> (Pallet: 20 boxes)
Fire resistance	Bfl-s1
Number of colours	6
Dimensional stability	EN 986 max. 0,20%
EN 1307	33 - LC1

