



SUITABLE FOR MEDIUM CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

MANUFACTURED IN BELGIUM //

## TECHNICAL SPECIFICATIONS //

Fibre	100% Olefin (Solution Dyed)
Construction	Tufted
Machine gauge	1/10" Loop Pile ("Multi-Roll")
Stitches per inch	12.6 (47 per 10 cm)
Pile thickness (DIN E-54325)	ca. 2 mm (low) and 4 mm (high)
Total thickness (DIN 53883 P.3)	ca. 6 mm
Total gross weight	680 g/sqm (20 Oz/sqyd)
Total weight	4,200 g/sqm (124 Oz/sqyd)
Density	ca. 185, 180 knots/sqm
Primary backing	Polyester
Secondary backing	Bitumen
Size per tile	50 x 50 cm
No. Of tiles per box	20 (= 5 sqm)
Installation	Surface Tackifier
Antistatic properties	Permanent Antistatic (< 2 kV))

## PERFORMANCE SPECIFICATIONS //

Flammability: NFP 92-501/NEP 92-507	M3
Flammability: BS 4790: 1987 (Hot Nut Metal)	Low radius of Ignition
Light Fastness (DIN 54004)	5-7
Water Fastness (DIN 54006)	3-5
Rubbing Fastness (DIN 54021)	3-5

## PILE DIRECTION //

Directional arrows are printed at the back of each tile. Best results are obtained when laid chequerboard (quarter-turn).

## LAYING INSTRUCTIONS //

Install using recommended surface tackifier adhesive.

## CLEANING //

Best results are obtained when using a professional shampoo or steam cleaning service.