



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% BCF Solution Dyed Synthetic
CONSTRUCTION	1/12" Loop Pattern
PILE WEIGHT	ca. 810g/m ² (24 oz/y ²)
TOTAL WEIGHT	ca. 4010g/m ² (118 oz/y ²)
PILE THICKNESS	ca. 3mm
TOTAL HEIGHT	ca. 7mm
BACKING	PVC - Free Synthetic Backing
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	24 pcs (6m ²)
ANTISTATIC PROPERTIES	Permanent Antistatic

PERFORMANCE SPECIFICATIONS //

As tested & certified by I.T.T.S. Inc., U.S.A.

FLAMMABILITY: Radiant Panel ASTM-E-648	>=0.45 (Class 1)
FLAMMABILITY: Methanamine Pill ASTM-D-2859	Self-Extinguishing
FLAMMABILITY: Smoke Density ASTM-E-662	<= 450
TUFT BIND (ASTM-D-1335)	7.6 lbs
STAIN RESISTANCE	10 No residual stain (AATCC-175-1993)
LIGHTFASTNESS (AATCC 16E)	5 (Negligible or no change)
COLORFASTNESS TO OZONE (AATCC-165)	5 (Negligible or no change)
DIMENSIONAL STABILITY (AACHEN TEST)	<= 2%
RECOMMENDED USAGE	Medium Commercial Use
RECOMMENDED INSTALLATION METHOD	Quarter Turn

A PREMIUM CARPET TILE

MANUFACTURED IN CHINA //

INSTALLATION GUIDELINES //

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load bearing. The manufacturer recommends that the carpet tiles be installed in a "checker board" pattern, that is, every 2nd carpet tile should be turned 90° to the tile laid prior to it. If uni-effect is desired, the tiles should be installed with the arrows in the same direction. However, the seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles.