



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% BCF Olefin (3 -Ply)
CONSTRUCTION	Tufted
MACHINE GAUGE	1/10" Loop Pile
STITCHES PER INCH	48
PILE THICKNESS (DIN E-54325)	ca. 3.0 mm
TOTAL THICKNESS (DIN 53883 P.3)	ca. 5.5 mm
PILE GROSS WEIGHT	ca. 610g/sqm (18 Oz/sqyd)
TOTAL WEIGHT	ca. 3500g/sqm (103 Oz/sqyd)
PRIMARY BACKING	Polyester Spunbonded
SECONDARY BACKING	Bitumen
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	24 (= 6 sqm)
INSTALLATION	Surface Tackifier/Permanent Glue
ANTISTATIC PROPERTIES	Permanent Antistatic

PERFORMANCE SPECIFICATIONS //

As tested & certified by I.T.T.S. Inc., U.S.A.

FLAMMABILITY: Radiant Panel ASTM-E-648	>=0.45 (Class 1)
FLAMMABILITY: Methanamine Pill ASTM-D-2859	Self-Extinguishing
FLAMMABILITY: Smoke Density ASTM-E-662	<= 450
TUFT BIND	6.5 lbs. / 104.0 ozs.
STAIN RESISTANCE	5 (Negligible or no stain)
CROCKING - WET & DRY (AATCC 165)	5 (Negligible or no stain)
LIGHTFASTNESS (AATCC 165)	5 (Negligible or no change)
COLORFASTNESS TO OZONE	5 (Negligible or no change)
DIMENSIONAL STABILITY (AACHEN TEST)	<= 2.4 %
RECOMMENDED USAGE	Medium Contract Use
RECOMMENDED INSTALLATION METHOD	Quarter Turn

MANUFACTURED IN CHINA //

A PREMIUM CARPET TILE

INSTALLATION GUIDELINES //

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load bearing. The manufacturer recommends that the carpet tiles be installed in a "checker board" pattern, that is, every 2nd carpet tile should be turned 90° to the tile laid prior to it. If uni-effect is desired, the tiles should be installed with the arrows in the same direction. However, the seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles.