



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% BCF Olefin (3 -Ply)
CONSTRUCTION	Tufted Graphics (Speckled Effect)
MACHINE GAUGE	1/10" Loop Pile
STITCHES PER INCH	41.3 per 10 cm
PILE THICKNESS (DIN E-54325)	ca. 4.0 mm (0.14")
TOTAL THICKNESS (DIN 53883 P.3)	ca. 7.0 mm (0.25")
TOTAL GROSS WEIGHT	ca. 880g/sqm (26 Oz/sqyd)
TOTAL WEIGHT	ca. 4700g/sqm (138 Oz/sqyd)
PRIMARY BACKING	Polyester Spunbonded
SECONDARY BACKING	Glass Fiber, PVC
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	20 (= 5 sqm)
INSTALLATION	Surface Tackifier
ANTISTATIC PROPERTIES	Permanent Antistatic

PERFORMANCE SPECIFICATIONS //

This product meets or exceeds the minimum performance specifications following independent laboratory tests:

FLAMMABILITY:	CNS 13592
COLOR FASTNESS TO LIGHT	CNS 13592 L4162-1995 7.5.1
COLORFASTNESS TO CROCKING	CNS 13592 L4162-1995 7.5.2
ABRASION RESISTANCE	CNS 13595 L3238-1995 Method 9, Load: 1 kg Abrading Wheel No. H38
HALF DECAY TIME (SEC)	JIS L1094-1996 A Method 25°C, 40% R.H.
DIMENSIONAL CHANGES	CNS 13924 L32492-1997 8 Condition: 24 hrs

A PREMIUM CARPET TILE

MANUFACTURED IN CHINA //

INSTALLATION GUIDELINES //

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load bearing. The manufacturer recommends that the carpet tiles be installed in a "checker board" pattern, that is, every 2nd carpet tile should be turned 90° to the tile laid prior to it. If uni-effect is desired, the tiles should be installed with the arrows in the same direction. However, the seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles.