



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% BCF Olefin (Solution Dyed)
CONSTRUCTION	Tufted Textured Hi-Low Graphics
MACHINE GAUGE	1/12" Loop Pile
STITCHES PER 10 CM	41.3 (10.5 per inch)
PILE THICKNESS (DIN E-54325)	ca. 4.0 mm (high), 3.5 mm (low)
TOTAL THICKNESS (DIN 53855/3)	ca. 7.0 mm (0.28")
PILE GROSS WEIGHT	ca. 815 g/sqm (24 Oz/sqyd)
TOTAL WEIGHT (DIN 53854)	ca. 6,250 g/sqm (185 Oz/sqyd)
BACKING	PVC + Glass Fiber Spunbonded
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	16 (= 4 sqm)
INSTALLATION	Surface Tackifier
WEAR WARRANTY	10 Year Limited Wear Warranty

PERFORMANCE SPECIFICATIONS //

As tested & certified by I.T.T.S. Inc., U.S.A.

FLAMMABILITY: Radiant Panel ASTM-E-648	>=0.45 (Class 1)
FLAMMABILITY: Methanamine Pill ASTM-D-2859	Self-Extinguishing
FLAMMABILITY: Smoke Density ASTM-E-662	<= 450
TUFT BIND	6.5 lbs. / 104.0 ozs.
STAIN RESISTANCE	5 (Negligible or no stain)
CROCKING · WET & DRY (AATCC 165)	5 (Negligible or no stain)
LIGHTFASTNESS (AATCC 165)	5 (Negligible or no change)
COLORFASTNESS TO OZONE	5 (Negligible or no change)
DIMENSIONAL STABILITY (AACHEN TEST)	<= 2.4 %
RECOMMENDED USAGE	Medium Contract Use
RECOMMENDED INSTALLATION METHOD	Quarter Turn

A PREMIUM CARPET TILE ISO 9002 CERTIFIED

MANUFACTURED IN CHINA //