



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% Olefin Solution Dyed
CONSTRUCTION	Tufted textured
MACHINE GAUGE	1/12" Loop Pile
STITCHES PER INCH	10.5
PILE THICKNESS (DIN E-54325)	5.5mm
TOTAL THICKNESS (DIN 53883 P.3)	7mm
TOTAL GROSS WEIGHT	815g/sqm
TOTAL WEIGHT	4700g/sqm
BACKING	PVC + glass fiber spunbonded
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	20
INSTALLATION	Surface Tackifier
ANTISTATIC PROPERTIES	Permanent Antistatic

PERFORMANCE SPECIFICATIONS //

FLAMMABILITY: NANS 21203	A3
NFP 92-501/NEP 92-507	M3
BS 4790: 1987 (Hot Nut Metal)	Low Radius of Ignition
LIGHT FASTNESS (DIN 54004)	7
WATER FASTNESS (DIN 54006)	4-5
RUBBING FASTNESS (DIN 54021)	4-5
HORIZONTAL RESISTANCE (DIN 54345)	-10 (11)
VERTICAL RESISTANCE (DIN 54345)	-10 (11)

A PREMIUM CARPET TILE

MANUFACTURED IN CHINA //