



SUITABLE FOR NORMAL CONTRACT USE: OFFICES, SHOPS, BANKS, SCHOOLS, HOSPITALS AND OTHER PUBLIC AREAS.



PERMANENTLY ANTISTATIC – ELECTROSTATIC SHOCK IS REDUCED TO A MINIMUM.



SUITABLE FOR AREAS WHERE ROLLER – CASTOR CHAIRS ARE USED (CHAIR PADS ARE RECOMMENDED).



SUITABLE FOR USE IN AREAS WHERE UNDERFLOOR HEATING IS USED



FLAME RETARDANT – DOES NOT CONTRIBUTE TO THE START OR SPREAD OF FIRE



SUITABLE FOR USE IN ROOMS WHERE PERSONAL COMPUTERS ARE INSTALLED.

TECHNICAL SPECIFICATIONS //

FIBRE	100% BCF Solution Dyed Nylon
CONSTRUCTION	Tufted Multi-Level Loop 1/12” Gauge (1/8 + 1/4)
PILE WEIGHT	ca. 880g/m ² (26 oz/y ²)
TOTAL WEIGHT	ca. 5000g/sqm
PILE THICKNESS	ca. 4mm (high), 3.50mm (medium), 3mm (low)
TOTAL HEIGHT	ca. 7mm
NUMBERS OF TUFTS	303360/sqm (Approx.)
PRIMARY BACKING	PES/PA Fleece (Non Woven Textile)
SECONDARY BACKING	Glass Reinforced PVC
SIZE PER TILE	50 x 50 cm
NO. OF TILES PER BOX	24 pcs (5m ²)
ANTISTATIC PROPERTIES	Permanent Antistatic

PERFORMANCE SPECIFICATIONS //

As tested & certified by I.T.T.S. Inc., U.S.A.

FLAMMABILITY	FF I-70 // 16CFR 1630 Pass 8/8 (ASTM-D-2859)
HEXAPOD TEST (WEAR)	+75% Pile Retention after 4000 Cycles (ASTM-D-552)
SMOKE DENSITY	Less than 450 (ASTM-E-662)
STATIC PROPENSITY	Under 3.5KV (AATCC-134)
SOIL PROPENSITY	Grey Scale 5 (AATC-123)
DIMENTIONAL STABILITY	Din 54318 < 0.20%
COLOURFASTNESS	5/5 on Grey Scale
RECOMMENDED USAGE	Medium Commercial Use
RECOMMENDED INSTALLATION METHOD	Quarter Turn

MANUFACTURED IN CHINA //

A PREMIUM CARPET TILE

INSTALLATION GUIDELINES //

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load bearing. The manufacturer recommends that the carpet tiles be installed in a “checker board” pattern, that is, every 2nd carpet tile should be turned 90° to the tile laid prior to it. If uni-effect is desired, the tiles should be installed with the arrows in the same direction. However, the seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles.