

Heritage Carpets

TOP SERIES

Specifications may vary slightly between designs in the Top Series.
Design and colour specification sheets available upon request

Specifications

Construction: 1/12" Tufted Loop Pile
Yarn Composition: 100% Solution Dyed BCF Nylon
Tufted Pile Weight: ca. 678 g/m² (20 oz/yd²) (+/- 15%)
Total Weight: ca. 3,400 g/m² (100 oz/yd²) (+/- 15%)
Pile Height: ca. 5 mm (+/- 0.5 mm)
Total Thickness: ca. 6.5 mm (+/- 0.5 mm)
Density (APYD): 3,656.5 ozs/yd³
Tuft Density: 180,000 stitches/m²
Stitch Rate: 47.5 per 10 cm
Backing: EcoAce® Backing (Polyolefin)
Backing Recyclability: 69% (By Weight)
Plank Size: 25 cm x 100 cm
Packing: 21 pcs per box (5.25 m²)

Performance

Stain Resistance: 10 (AATCC-175-03)
Static Control: Pass - Max. 4 kV (AATCC-134-1996)
Tuft Bind: Pass - 6.8 lbs (ASTM-D-1335)
Dimensional Stability: Pass - Max. 0.2% change (EN 986 (2005))
Indoor Air Quality (V.O.C.): Pass - No VOC Detected (ASTM-D5116-10)
Impact Sound Insulation: ΔL_w: 28 dB (ISO 10140)
Sound Absorption: α_w = 0.25 (H) (ISO 354)
Hz: 125, 250, 500, 1000, 2000, 4000
α_s: 0.00, 0.05, 0.30, 0.20, 0.20, 0.25
Antibacterial: Pass - AATCC 174-II (2016)
Castor Chair: Pass - EN 985-Test A (2001)
Thermal Resistance: Pass - ISO 8302 (1991), EN 12667 (2001)
Resistance to Fraying: Pass - EN ISO 10833 (2019)
Flammability:
- **Reaction to Fire Classification:** Bfl-s1 (EN 13501-1 (2019))
- **Radiant Panel:** Pass - Class I (ASTM-E-648-19a)
- **Pill Test:** Pass - 8 (ASTM-D-2859-96)
Colourfastness:

Heritage Carpets

- **To Light:** Excellent - 5 (AATCC-16E)
- **To Wet & Dry Crocking:** Excellent - 5 (AATCC-165)
- **To Ozone:** 3 (AATCC-129)

Warranty

15 Year Carpet Wear Warranty

Lifetime Anti-shock Carpet Warranty

Product Advisory Note:

Ensure the subfloor is clean, dry, smooth, level, dust-free, and capable of supporting loads without compression. Apply seam sealant where required during installation. Due to dye lot variations, actual colours may differ slightly from samples. Chair pads are recommended to reduce carpet wear.

Ideal for Heavy Commercial Use.

Environment:

The design and production of Top Collection Tile adhere to the ISO 14001:2004 Environmental Management System and comply with all environmental regulations. As a responsible manufacturer, we strive to minimise our carbon footprint. A majority of our excess production materials are recycled in-house, resulting in at least 10% recycled content in our tile backing. Additionally, Top Collection Tile is free from PVC in both its materials and packaging. Top Collection Tile is an environmentally friendly “green” carpet.